10K DUCTILE IRON, GLOBE VALVES

Fig: 600AT/10-DD-N Sizes: 3/8-2inch(10-50mm)

SOFT SEAT, SCREWED BONNET, INSIDE SCREW, SCREWED ENDS.

Standards

End to End: JIS B2051 (2)End Connection: JIS B0203Wall Thickness: JIS B2051 (2)

Test Standard

. MANUFACTURERS STANDARD

Dimensions

2 1 1110 110 1 0 110						
SIZE(inch/mm)		L	L1	Н	D1	Kg
3/8	10	55.0	0.0	108.0	60.0	0.00
1/2	15	65.0	0.0	123.0	70.0	0.00
3/4	20	80.0	0.0	123.0	80.0	0.00
1	25	90.0	0.0	144.0	90.0	0.00
11/4	32	105.0	0.0	159.0	100.0	0.00
11/2	40	120.0	0.0	178.0	115.0	0.00
2	50	140.0	0.0	197.0	135.0	0.00

Material List

NAME OF PART	MATERIAL	SPECIFICATION	
ВОДУ	DUCTILE IRON	FCD-S	
BONNET	DUCTILE IRON	FCD-S	
STEM	STAINLESS STEEL	SUS420J2	
DISC	G/F.PTFE		


Specifications

10K DUCTILE IRON, GLOBE VALVES, SOFT SEAT, SCREWED BONNET, INSIDE SCREW, SCREWED ENDS.

End to End: JIS B2051 (2), End Connection: JIS B0203, Wall Tchickness: JIS B2051 (2), Test Standard: MANUFACTURERS STANDARD, Sizes: 3/8-2inch(10-50mm), B0DYMATERIAL: DUCTILE IRON, B0NNETMATERIAL: DUCTILE IRON, STEMMATERIAL: STAINLESS

STEEL, DISCMATERIAL : G/F. PTFE, Fig : 600AT/10-DD-N





For more details, please refer to the drawing.

Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



