## CLASS 125 CAST IRON GATE VALVE FLANGED ENDS

Fig: 514/125-FSRF Sizes: 2-12inch(50-300mm)

BOLTED BONNET, OUTSIDE SCREW & YOKE, FLAT FACE FLANGED ENDS.

Standards

• End to End: ASME B16.10 CLASS 125 • End Connection: ASME B16.1 CLASS 125

. Wall Thickness: -Test Standard. KITZ STANDARD

## Dimensions

SIZE(inch/mm)		L	L1	Н	D1	Kg
2	50	178.0	0.0	329.0	160.0	0.00
21/2	65	190.0	0.0	383.0	180.0	0.00
3	80	203.0	0.0	437.0	180.0	0.00
4	100	229.0	0.0	534.0	230.0	0.00
5	125	254.0	0.0	629.0	230.0	0.00
6	150	267.0	0.0	727.0	250.0	0.00
8	200	292.0	0.0	920.0	280.0	0.00
10	250	330.0	0.0	1135.0	360.0	0.00
12	300	356.0	0.0	1364.0	450.0	0.00

## Material List


NAME OF PART	MATERIAL	SPECIFICATION	
BODY	CAST IRON	FC200	
BONNET	CAST IRON	FC200	
STEM	FORGED BRASS	C3771	
DISC	CAST IRON	FC200	



CLASS 125 CAST IRON GATE VALVE FLANGED ENDS, BOLTED BONNET, OUTSIDE SCREW & YOKE, FLAT FACE FLANGED ENDS.

End to End: ASME B16.10 CLASS 125, End Connection: ASME B16.1 CLASS 125, Wall Tchickness: -, Test Standard: KITZ STANDARD, Sizes: 2-12inch(50-300mm), BODYMATERIAL: CAST IRON, BONNETMATERIAL: CAST IRON, STEMMATERIAL: FORGED BRASS, DISCMATERIAL: CAST IRON, Fig: 514/125-FSRF





Pressure-temperature ratings and other performance data published in this catalog have been developed from our design calculation, in-house testing, field reports provided by our customers and/or published official standards or specifications. They are good only to cover typical applications as a general guideline to users of KITZ products introduced in this catalog. For any specific application, users are kindly requested to contact KITZ Corporation for technical advice, or to carry out their own study and evaluation for proving suitability of these products to such an application. Failure to follow this request could result in property damage and/or personal injury, for which we shall not be liable. Read instruction manual carefully before use.



